

Agw

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
7 August 2003 (07.08.2003)

PCT

(10) International Publication Number
WO 03/064891 A1

(51) International Patent Classification⁷: F16H 13/08

(21) International Application Number: PCT/US03/00407

(22) International Filing Date: 7 January 2003 (07.01.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/354,010 31 January 2002 (31.01.2002) US
60/374,746 23 April 2002 (23.04.2002) US

(71) Applicant: THE TIMKEN COMPANY [US/US]; 1835
DUEBER AVENUE SW, CANTON, OH 44706-0930
(US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


(72) Inventor: AI, Xiaolan; 4480 NOBLE LOON, MASSIL-
LON, OH 44646 (US).

Published:
— with international search report

(74) Agent: WARREN, Douglas E; POLSTER, LIEDER,
WOODRUFF & LUCCHESI, L.C., 763 SOUTH NEW
BALLAS ROAD, ST. LOUIS, MO 63141 (US).

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: ECCENTRIC PLANETARY DRIVE TRANSMISSION



(57) Abstract: An eccentric planetary traction drive transmission (A) which includes at least two planetary rollers (3 & 4), sun roller member (2), and a carrier member (27). One of the planetary rollers (3, 4, or 5) is flexible and is positioned between and in contact with an outer ring member (1) and the sun roller member (2). Rotation of either the outer ring member (1) or the sun roller member (2) wedges the flexible planetary roller (3, 4, or 5) within a convergent wedge gap (23) which squeezes the flexible planetary roller (3, 4, or 5) between the outer ring member (1) and the sun roller member (2). Friction between the flexible planetary roller (3, 4, or 5), the sun roller member (2), and the outer ring member (1) transmits rotational motion and torque between the outer ring member (1) and the sun roller member (2). The other at least one supporting planetary roller (3, 4, or 5) is a supporting roller which supports the sun roller member (2) and the carrier member (27). A plurality of bearings (26) supports the sun roller member (2) within the outer ring member (1) and the at least one supporting planetary roller (3, 4, or 5).

WO 03/064891 A1

ECCENTRIC PLANETARY DRIVE TRANSMISSION

MECHANISM

Technical Field

5 This invention relates in general to a planetary traction drive transmission, and, more particularly, to a planetary traction drive transmission with at least one flexible roller having an adaptive self-loading mechanism.

Background Art

 Traction drives use frictional force to transmit torque and power.
10 Because the power is transmitted between two smooth surfaces, often through a thin layer of lubricant, a traction drive possesses unique characteristics that are not readily attainable by gear drives. These characteristics include quietness, high-efficiency, high rotational accuracy, and zero-backlash.

 Generating adequate normal force at the contact is essential for traction
15 drives. Various loading mechanisms have been proposed. These mechanisms have lead to a host of designs. A common practice is to use tapered surfaces along the axial direction. By moving these surfaces axially, a radial displacement and thus normal force are generated. Examples of such designs are disclosed in U.S Patent Numbers 3,475,993 and 3,375,739.

20 Since the envelopes of the tapered surfaces in most designs do not necessarily converge to a common point, this results in a so-called spin motion at contacting surfaces. The spin motion not only offsets the high-efficiency otherwise provided by the traction drive, but also causes component wear and high break away torque.

25 Recently, a design of zero-spin planetary traction drive has been proposed by Ai as disclosed in the U.S. Patent Number 6,095,940. This design employs the on-apex concept similar to that of tapered roller bearings. Two rows of planetary rollers are used to balance the internal axial force on the planetary rollers. Although this design offers a torque actuated loading
30 mechanism and greater torque capability, it is somewhat complex in construction.

-2-

The cylindrical planetary traction drive is also able to achieve zero-spin motion. However, generating sufficient normal force at the contacts has been a challenge. Designs proposed in the past have offered various means to pre-load the drive either by mechanically deforming the outer rings or by thermal assembling the drive. The pre-load generated by such means, in general, can not be adjusted during operation. For partial load application, traction drives are unnecessarily overloaded. This has a negative impact on transmission efficiency and service life.

Perhaps the simplest means to generate torque responsive load is using eccentric planetary drives as was disclosed by Dieterich U.S. Patent Number 1,093,922 in 1914. Over the years, various improvements have been proposed. See for example, U.S. Patent Numbers 3,945,270, 4,481,842, 4,555,963, and foreign patent numbers JP10-311398, EP 0,856,462 A2. They all have multiple planetary rigid rollers, and each planetary roller requires a supporting shaft.

While friction actuated loading mechanisms have been disclosed in prior art where one of the planetary rollers was entrained by friction force into the wedged-space created by eccentric raceways, the loading roller was rigid and thus the entrainment angle was kept constant. This was based on the notion that the maximum traction coefficient was constant during the operation. The entrainment angle was determined based on a specified friction coefficient, which was assumed to be not a function of the contact load. Such a loading mechanism was either over conservative or inadequate when the maximum available traction coefficient changes with contact load.

For eccentric planetary drives, the planetary rollers have different sizes. In most of the prior art designs, this has led to different contact stresses at the contact between the sun roller and planets.

In some designs proposed in prior art, the drive had more than one loading roller that is moveable. This could cause a change in eccentricity between input and output shafts as the loading rollers adjusted their positions.

Therefore, it is desirable to provide a simple and improved design that allows for an adaptive, torque responsive loading mechanism where the entrainment angle changes as the load varies to match the variation in the

maximum available traction coefficient, a design that offers balanced contact stresses for all planet rollers, and a design that reduces or eliminates the change in eccentricity as the loading roller is adjusting its position.

Summary of the Invention

5 This patent application relates to planetary traction drives in general and specifically to an eccentric, cylindrical planetary traction drive having at least one flexible planetary roller capable of providing an adaptive self-loading mechanism to facilitate the transfer of rotational motion and torque. The current invention also provides a traction drive that allows for an adaptive
10 torque responsive loading and also provides a traction drive with well-balanced contact stresses at the most critical contacts.

Brief Description of Drawings

FIG. 1 is a front view of the present invention.

FIG. 2 is a left side sectional view of the present invention.

15 FIG. 3 is an oblique sectional view of the present invention.

FIG. 4 is an exploded view of the present invention.

FIG. 5 is a graphical representation of the mathematical relationship between various components of the present invention.

20 FIG. 6 is a graphical representation of the normal forces between the components of the present invention.

FIG. 7 is a graph showing the relationship between the contact load and the geometry/traction coefficient of the present invention.

FIG. 8 is a front view of a second embodiment of the present invention.

25 FIG. 9 is a left side sectional view of a second embodiment of the present invention.

FIG. 10 is an oblique sectional view of a second embodiment of the present invention.

FIG. 11 is an exploded view of a second embodiment of the present invention.

30 Corresponding reference characters indicate corresponding parts throughout the several views of the drawings.

Best Mode for Carrying Out the Invention

Referring now to Figures 1 and 2, one embodiment of the cylindrical planetary traction drive A comprises an outer ring member 1, a sun roller member 2, a first planetary roller 5, two second planetary rollers 3 & 4, and a carrier member 27. The outer ring member 1 further comprises a first cylindrical raceway 9 surrounding the axis of rotation, and a first fixed flange 10 and a second fixed flange 11.

The sun member 2 includes a second cylindrical raceway 12, a third fixed flange 13, a fourth fixed flange 14, and a shaft 15. The first planetary roller 5 has a third cylindrical raceway 16, and the second planetary rollers 3 and 4 have a fourth cylindrical raceway 18 and 17 (Figure 4) respectively. The first planetary roller 5 and the two second planetary rollers 3 and 4 are placed between and in contact with first cylindrical raceway 9 and second cylindrical raceway 12.

At least one of either the planetary roller 5 or the planetary rollers 3 and 4 is flexible compared to other rollers. In the embodiment shown herein, the first planetary roller 5 is the flexible roller and serves as a loading roller. Thus, it will hereafter be called the loading planetary roller 5. The loading planetary roller 5 deforms noticeably when diametrically squeezed.

At least one of the second planetary rollers 3 and 4 is a supporting roller. The supporting roller is relatively rigid and hardly deforms under diametrical load. In the embodiment shown herein, both planetary rollers 3 and 4 are supporting rollers and will hereafter be called the supporting planetary rollers 3 and 4. The supporting planetary rollers 3 and 4 are firmly fixed by shafts 22 and 25 respectively to the carrier member 27. Each of the supporting planetary rollers 3 and 4 is mounted onto its respective shaft 22 or 25 with a bearing 26 and two snap rings 24.

The carrier member 27 contains a base plate 6 and a cover plate 7. There are extrusions 19, 20, and 21 protruding perpendicularly from the back face of the base plate 6. The cover plate 7 is fastened to the top of the extrusions using fasteners 8, forming cavities for receiving the loading planetary roller 5 and the supporting planetary rollers 3 and 4. The first cylindrical

raceway 9 on the outer ring member 1 is eccentric to the second cylindrical raceway 12 on the sun member 2. The space between the first cylindrical raceway 9 and the second cylindrical raceway 12 forms a wedge gap 23 (Fig. 5).

The width of the wedged-gap h is expressed as:

$$h = 2r \cos \frac{\delta}{2} \quad (1a)$$

It can be approximated by the following cosine function:

$$h \approx R_2 - R_1 + e \cos \alpha_1 \quad (1b)$$

where R_1 is the radius of the sun roller raceway 12; R_2 is the radius of the first cylindrical raceway 9; and e represents the eccentricity between the raceways 12 & 9 of the sun roller member and the outer ring.

The wedge angle δ for planetary roller at azimuth position α_1 is given by:

$$\delta = \text{Arc cos} \left[\frac{(R_1 + r)^2 + (R_2 - r)^2 - e^2}{2(R_1 + r)(R_2 - r)} \right] \quad (2)$$

where r is the effective radius of the planetary roller at this azimuth position, and can be expressed in terms of α_1 as:

$$r = \frac{R_2^2 - R_1^2 - e^2 + 2eR_1 \cos \alpha_1}{2(R_2 + R_1 - e \cos \alpha_1)} \quad (3a)$$

The wedge angle δ represents a contact geometry condition.

The geometry coefficient μ_G is defined as:

$$\mu_G = \tan \left(\frac{\delta}{2} \right) \quad (4)$$

As can be seen from equations (1) to (4), for α_1 between 0 and 90 (or 0 and -90), when α_1 moves away from the $\alpha_1 = 0$ position, the width of the gap h reduces, the wedge angle increases and thus geometry coefficient μ_G increases.

In the embodiment shown in FIG. 1, the flexible loading planetary roller 5 is assembled in the wedge gap 23 at an azimuth angle between $\alpha_1 = -90$ to 90 degrees, preferably in vicinity of $\alpha_1 = 0$. The center of the flexible loading planetary roller 5 is left floating along the wedge gap 23. The flexible loading planetary roller 5 is sufficiently flexible in the radial direction. When squeezed,

its effective diameter reduces in the corresponding direction. It is recommended that at home position, $\alpha_1 = 0$, the flexible loading planetary roller 5 is slightly squeezed.

The supporting planetary rollers 3 and 4 are arranged in wedge gap 23 generally between azimuth positions of $\alpha_1 = 90$ to 270 degrees. The centers of each of the supporting planetary rollers 3 and 4 are fixed to the carrier member 27.

The planetary traction drive A is preferred to operate with the carrier member 27 stationary. During operation, the traction force tangent to the third cylindrical raceway 16 of the loading planetary roller 5 always drags the loading planetary roller 5 into the convergent wedge gap 23. The loading planetary roller 5 is thus squeezed, generating substantial contacting force normal to the contact surfaces. If the eccentricity e in relationship to geometry of the planetary train is favorable, a balance is achieved where the maximum available traction force is equal to or greater than the operating traction force. This condition is called frictional self-loading. The relationship for ensuring such fictional self-loading is set forth by:

$$\mu_G \leq \mu_T \quad (5a)$$

where μ_T is the maximum available friction coefficient at the contacts.

For optimal efficiency and service life of the planetary traction drive A, it is always desirable to have geometry coefficient μ_G close to but slightly smaller than the maximum available traction coefficient μ_T under various load conditions. That is:

$$\mu_G \lesssim \mu_T \quad (5b)$$

During operation, the loading planetary roller 5 is entrained into the convergent wedge gap 23 and squeezed. Consequently, the effective diameter (or radius) of the loading planetary roller 5 reduces. The loading planetary roller 5 thus moves to a new azimuth position, establishing a new balance. At the new position, the width of wedge gap 23 is narrower and the contact geometry coefficient μ_G is increased.

-7-

The diametrical reduction of the loading planetary roller 5 can be estimated by:

$$2dr = \left(\frac{\pi}{4} - \frac{2}{\pi} \right) \frac{Wr^3}{EI} \quad (6)$$

where W is the contact load; E is the Young's elastic modulus; and I is the area
5 moment of inertia of ring cross section for the flexible first planetary roller 5.

The geometry coefficient μ_G corresponding to this diametrical reduction is:

$$\mu_G = \tan \left\{ \frac{1}{2} \text{Arc cos} \left[\frac{(R_1 + R_2 + e - 2dr)^2 + (R_1 + R_2 - e + 2dr)^2 - 4e^2}{2(R_1 + R_2 + e - 2dr)(R_1 + R_2 - e + 2dr)} \right] \right\} \quad (7a)$$

With equations (6) and (7a), the increase in geometry coefficient μ_G with
10 the contact load can be quantified. Figure 7 shows the variation of μ_G , with contact load W for planetary rollers with different cross section moments of inertia I .

The maximum geometry coefficient is bounded by

$$\mu_{G \max} = \tan \left\{ \frac{1}{2} \text{Arc cos} \left[1 - 2 \left(\frac{e}{R_1 + R_2} \right)^2 \right] \right\} \quad (7b)$$

15 On the other hand, a large body of research results (Tevaarwerk, NASA CR-165226, 1981) showed that the maximum available traction coefficient μ_T increases with contact pressure or contact load. The change in μ_T with contact load for a traction fluid is also plotted in Figure 7 with symbols and a dotted line.

20 The flexible, floating planetary roller design of the current invention thus provides an opportunity for an adaptive frictional self-loading mechanism. That is, to adaptively change contact geometry coefficient to match the change in maximum available traction coefficient. As a result, not only constrain (5a) can be met, but also the geometry coefficient can be kept close to the maximum
25 available traction coefficient (constraint (5b)) for the entire load spectrum. Adaptive self-loading can be achieved by choosing a flexible planetary roller with adequate cross section moment of inertia I . With this flexible roller it is possible to the change contact geometry coefficient and have the change match

or compensate for the change in the maximum available traction coefficient when contact load changes. For example, the second curve in Figure 7 with $I = 13 \text{ mm}^4$ matches the change in maximum traction coefficient. This curve demonstrates the adaptive design principle.

5 The flexible loading planetary roller 5 can be as simple as a ring, however, other design alternatives are also possible.

 The torque capacity of a traction drive is determined by the maximum allowable stress at the contact. Since planetary rollers for an eccentric planetary traction drive may have different sizes, the maximum contact stress for each
10 planetary roller is not necessarily the same. To improve fatigue life, it is desirable to select the planetary roller size and place these rollers in proper azimuth positions so that every planetary roller has approximately the same contact stress.

 Assume under a specified load (usually the maximum weighted load),
15 the effective radius of the flexible loading planetary roller 5 is r_5 (after being squeezed), and its azimuth position is α_5 (see Figure 6). The radii of the supporting planetary rollers 3 and 4 are determined from the following equations in conjunction with equation (3).

$$\bar{R}_3 \sin(\alpha_5 - \alpha_3) + \bar{R}_4 \sin(\alpha_5 - \alpha_4) = 0 \quad (8)$$

$$20 \quad \bar{R}_3 \cos(\alpha_5 - \alpha_3) + \bar{R}_4 \cos(\alpha_5 - \alpha_4) + \bar{R}_5 = 0 \quad (9)$$

where $\bar{R}_i = \frac{R_1 \cdot r_i}{R_1 + r_i}$ ($i = 3, 4, \text{ or } 5$) represents the composite contact radii for contact between the sun roller 2 and the planetary rollers 3, 4, and 5, respectively.

 The geometry relationship between the radius and azimuth position of
25 any supporting planetary roller is given by equation (3). That is:

$$r_i = \frac{R_2^2 - R_1^2 - e^2 + 2eR_1 \cos \alpha_i}{2(R_2 + R_1 - e \cos \alpha_i)} \quad (3b)$$

Subscript $i = 3$ and 4 refers to the supporting planetary rollers 3 and 4 respectively. To avoid edge stress, first cylindrical raceway 9 and second cylindrical raceway 12 are may be crowned. Or, alternatively, the third and

fourth cylindrical raceways 16, 17, and 18 of the planetary rollers 3, 4, and 5 may be crowned.

The outer surface of the outer ring member 1 can have gear teeth to communicate motion of rotation to a driving or driven component.

5 Alternatively, the outer surface of the outer ring member can be made into a pulley to communicate motion of rotation to a belt.

A second embodiment of the current invention is shown in Figures 8 through 11. The second embodiment comprises an outer ring member 101, a sun roller member 102, two supporting planetary rollers 103 and 104, a flexible
10 loading planetary roller 105, a carrier member 127, and a housing 130. The outer ring member 101 includes a first cylindrical raceway 109, and a shaft 133 supported on the housing 130 through a double row ball bearing 131. The sun roller member 102 has a second cylindrical raceway 112 and a shaft 115. The shaft 115 is supported on the carrier 127 by a ball bearing 132.

15 The second cylindrical raceway 112 on the sun roller member 102 is surrounded by and set eccentric to the first cylindrical raceway 109 in the outer ring member 101. The two supporting planetary rollers 103 and 104 are arranged in the wedge gap between the second cylindrical raceway 112 and the first cylindrical raceway 109. Each supporting planetary roller 103 and 104 has
20 a shaft 122 that is fixed to the carrier member 127. The supporting rollers are supported on the shaft 122 by bearings 126. The flexible loading roller 105 is arranged in the wedge gap between the two supporting rollers. The center of the flexible roller is free to rotate along the wedge gap.

The carrier member 127 includes a base plate 106 and a cover plate 107.
25 The base plate 106 has three protrusions 119, 120, and 121. The cover plate 107 is bolted to the protrusions on the base plate 106. The carrier member 127 is mounted to the housing 130 by a fastening means such as bolts. Bearing 131 is axially located by a snap ring 134 and a shoulder 136 in the housing 130. Bearing 132 is axially fixed by a snap ring 135 and a shoulder 137 in the carrier
30 member 127.

Claims

1. A planetary traction drive transmission comprising:
an outer ring member;
a carrier member;
5 a sun roller member eccentric to the outer ring member;
at least one loading planetary roller; and
at least one supporting planetary roller wherein one of either the at least
one loading planetary roller or the at least one supporting
planetary roller is sufficiently flexible in the radial direction to
10 communicate the rotational motion between the outer ring
member and the sun roller member and to effectively change the
geometry coefficient as load changes.
2. The planetary traction drive transmission of claim 1 wherein the
outer ring member further comprises an axis of rotation and a first cylindrical
15 raceway surrounding the axis of rotation.
3. The planetary traction drive transmission of claim 2 wherein the
sun roller member further comprises a first shaft and a second cylindrical
raceway, the second cylindrical raceway being eccentric to the first cylindrical
raceway to form a convergent wedge between the said first and second
20 cylindrical raceway.
4. The planetary traction drive transmission of claim 3 wherein the
at least one loading planetary roller includes a third cylindrical raceway and
each of the at least one supporting planetary roller has a fourth cylindrical
raceway.
- 25 5. The planetary traction drive transmission of claim 4 further
comprising at least one support shaft for supporting the at least one supporting
planetary roller in the carrier member.
6. The planetary traction drive transmission of claim 5 wherein
the carrier member includes a base plate, a cover plate, and at least two
30 fasteners,
the base plate having at least two extrusions protruding from the back
surface of the base plate,

-11-

the at least two extrusions being sized and located on the base plate such as to form cavities for receiving the at least one loading planetary roller and the at least one supporting planetary roller, each of the at least two extrusions also having a threaded hole therein,

5 the cover plate having a set of mounting holes located in the cover plate such that each of the set of mounting holes aligns with one of the threaded holes in the at least two extrusions, and

wherein the base plate has a first set of support shaft openings and the cover plate has a second set of support shaft openings, both sets

10 of support shaft openings being sized and located to accept the at least one support shaft for the at least one supporting planetary roller.

7. The planetary traction drive transmission of claim 6 wherein each of the at least one supporting planetary roller is supported on its respective support shaft by a bearing, and further comprising a means for retaining the bearing onto the individual support shaft of each of the at least one supporting planetary roller.

15

8. The planetary traction drive transmission of claim 7 wherein the at least one loading planetary roller is assembled in the convergent wedge gap at an azimuth angle between $\alpha_l = -90$ to 90 degrees and the center of the at least one loading planetary roller is free floating along the convergent wedge gap.

20

9. The planetary traction drive transmission of claim 8 wherein the at least one supporting planetary roller is arranged in the convergent wedge gap generally at an azimuth angle between $\alpha_s = 90$ to 270 degrees and the center of each of the at least one supporting planetary roller is fixed in relation to the carrier member.

25

10. The planetary traction drive transmission of claim 9 wherein the wedge angle δ for the at least one loading planetary roller at azimuth position α_l is characterized by

30

$$\delta = \text{Arc cos} \left[\frac{(R_1 + r)^2 + (R_2 - r)^2 - e^2}{2(R_1 + r)(R_2 - r)} \right]$$

-12-

where:

R_1 is the radius of the second cylindrical raceway of the sun roller member;

5 R_2 is the radius of the first cylindrical raceway of the outer ring member;

e represents the eccentricity between the first cylindrical raceway and the second cylindrical raceway; and

r is the effective radius of the at least one loading planetary roller at this azimuth position and is expressed in terms of α_1 as:

$$10 \quad r = \frac{R_2^2 - R_1^2 - e^2 + 2eR_1 \cos \alpha_1}{2(R_2 + R_1 - e \cos \alpha_1)}$$

11. The planetary traction drive transmission of claim 10 wherein a geometry coefficient μ_G is set to vary with the contact load through change in the wedge angle δ to provide an adaptive loading mechanism and the geometry coefficient μ_G is characterized by

$$15 \quad \mu_G = \tan\left(\frac{\delta}{2}\right)$$

12. The planetary traction drive transmission of claim 11 wherein the variations in the geometry coefficient μ_G is induced mainly by a diametrical reduction of the at least one loading planetary roller as the at least one loading planetary roller is squeezed within the convergent wedge gap where the
20 diametrical reduction is characterized by

$$2dr = \left(\frac{\pi}{4} - \frac{2}{\pi}\right) \frac{Wr^3}{EI}$$

where:

W is the contact load;

E is the Young's elastic modulus; and

25 I is the area moment of inertia of ring cross section for the at least one loading planetary roller.

13. The planetary traction drive transmission of claim 12 wherein the geometry coefficient μ_G is set to closely match the change in a maximum

-13-

available traction coefficient μ_T as the load changes and the geometry coefficient μ_G corresponding to the diametrical reduction of the at least one loading planetary roller is characterized by

$$5 \quad \mu_G = \tan \left\{ \frac{1}{2} \text{Arc cos} \left[\frac{(R_1 + R_2 + e - 2dr)^2 + (R_1 + R_2 - e + 2dr)^2 - 4e^2}{2(R_1 + R_2 + e - 2dr)(R_1 + R_2 - e + 2dr)} \right] \right\}$$

14. The planetary traction drive transmission of claim 13 wherein the maximum geometry coefficient μ_{Gmax} is set to be no greater than the maximum possible traction coefficient μ_T and the maximum geometry coefficient μ_{Gmax} is characterized by

$$10 \quad \mu_{Gmax} = \tan \left\{ \frac{1}{2} \text{Arc cos} \left[1 - 2 \left(\frac{e}{R_1 + R_2} \right)^2 \right] \right\}$$

15. The planetary traction drive transmission of claim 14 wherein radii for the at least one supporting planetary roller is characterized by

$$\bar{R}_3 \sin(\alpha_5 - \alpha_3) + \bar{R}_4 \sin(\alpha_5 - \alpha_4) = 0$$

$$\bar{R}_3 \cos(\alpha_5 - \alpha_3) + \bar{R}_4 \cos(\alpha_5 - \alpha_4) + \bar{R}_5 = 0$$

15 where:

α_5 = the azimuth position of the at least one loading planetary roller;

α_3 = the azimuth position of one of the at least one supporting planetary roller;

20 α_4 = the azimuth position of the other of the at least one supporting planetary roller;

$$\bar{R}_3 = \frac{R_1 \cdot r_3}{R_1 + r_3} \text{ where } R_1 \text{ is the radius of the second cylindrical}$$

raceway of the sun roller member and r_3 is radius of one of the at least one supporting planetary roller;

$$25 \quad \bar{R}_4 = \frac{R_1 \cdot r_4}{R_1 + r_4} \text{ where } R_1 \text{ is the radius of the second cylindrical}$$

-14-

raceway of the sun roller member and r_4 is the radius of the other at least one supporting planetary roller;

$$\overline{R}_s = \frac{R_1 \cdot r_s}{R_1 + r_s} \text{ where } R_1 \text{ is the radius of the second cylindrical}$$

raceway of the sun roller member cylindrical raceway

5 and r_s is the radius of the at least one planetary roller;

16. The planetary traction drive transmission of claim 15 wherein the geometric relationship between the radius and azimuth position of each of the at least one supporting planetary roller is characterized by

$$r_i = \frac{R_2^2 - R_1^2 - e^2 + 2eR_1 \cos \alpha_i}{2(R_2 + R_1 - e \cos \alpha_i)}$$

10 Where:

α_i = the azimuth position of the at least one planetary roller

r_i = the radius of one of the at least one planetary roller

17. The planetary traction drive transmission of claim 16 wherein the moment of inertia of the material from which the at least one loading planetary
15 roller is made allows the loading planetary roller to deform such that the change in the geometry coefficient either matches or nearly matches the change of maximum available traction coefficient due to changes in the contact load between the at least one loading planetary roller and the outer ring member, and between the at least one loading planetary roller and the sun roller member.

20 18. The planetary traction drive transmission of claim 17 wherein the first cylindrical raceway and the second cylindrical raceway are slightly crowned.

19. The planetary traction drive transmission of claim 17 wherein the third cylindrical raceway of the at least one loading planetary roller and at least
25 one of the fourth raceways of the at least one supporting planetary roller is slightly crowned.

20. A method of transmitting rotational motion and torque comprising the steps of:

-15-

installing a sun roller member into an outer ring member such that the sun roller member is eccentric to the outer ring member and a convergent wedge gap is formed between the sun roller member and the outer ring member; using one of a material or a combination of materials for at least one

5 loading planetary roller which has sufficient flexibility to create adaptive frictional self-loading between the at least one loading planetary roller and the outer ring member and the at least one loading planetary roller and the sun roller member;

installing the at least one loading planetary roller member into the

10 convergent wedge gap such that the at least one loading planetary roller member is between and in contact with the sun roller member and the outer ring member;

installing the at least one supporting planetary roller to support the sun roller member on a carrier member; and

15 wedging the at least one loading planetary roller member between the outer ring member and the sun roller member by rotation of either one of the sun roller member or outer ring member such that rotation and torque is transmitted between the outer ring member and the sun roller member.

20

1/7




FIG. 1




FIG. 2




FIG. 3

2/7





FIG. 4



4/7




FIG. 6

5/7




FIG. 7

6/7







FIG. 8



INTERNATIONAL SEARCH REPORT

Internat'l Application No
PCT/US 03/00407A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 F16H13/08

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 F16H

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 3 945 270 A (NELSON BERTEL S ET AL) 23 March 1976 (1976-03-23) cited in the application column 3, line 63 -column 4, line 9; figures 1-3 column 5, line 13-45 column 6, line 33-68 column 7, line 35-41	1-5, 20
A	---	6, 7
X	PATENT ABSTRACTS OF JAPAN vol. 1999, no. 03, 31 March 1999 (1999-03-31) & JP 10 331933 A (SANYO ELECTRIC CO LTD), 15 December 1998 (1998-12-15) abstract --- -/--	1-5, 20

☒ Further documents are listed in the continuallion of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

7 May 2003

Date of mailing of the international search report

19/05/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Szodfridt, T

INTERNATIONAL SEARCH REPORT

Internat Application No

PCT/US 03/00407

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 856 462 A (NSK LTD) 5 August 1998 (1998-08-05) cited in the application page 5, line 50-54; figures 3,4,7,16,17 page 6, line 21 -page 8, line 31 page 13, line 57 -page 14, line 54	1-7
X	---	20
A	US 4 481 842 A (NELSON BERTEL S) 13 November 1984 (1984-11-13) cited in the application column 2, line 28 -column 4, line 11; figures 1,2	1-5
X	---	20
A	DE 24 58 762 A (LANGE WOLF DIETER) 16 June 1976 (1976-06-16) page 3, paragraph 2 -page 6, paragraph 3; figures 1,2	1-4
X	-----	20

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US 03/00407

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 3945270	A	23-03-1976	NONE	
JP 10331933	A	15-12-1998	NONE	
EP 0856462	A	05-08-1998	JP 10252851 A	22-09-1998
			JP 10252853 A	22-09-1998
			JP 10271748 A	09-10-1998
			JP 10281248 A	23-10-1998
			JP 10281249 A	23-10-1998
			JP 10281250 A	23-10-1998
			JP 10316081 A	02-12-1998
			EP 0856462 A2	05-08-1998
US 4481842	A	13-11-1984	US 4555963 A	03-12-1985
DE 2458762	A	16-06-1976	DE 2458762 A1	16-06-1976

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER: _____**

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.